

Pan/Tilt Wireless Camera

ADC-V610PT

The ADC-V610PT is a wireless IP Pan/Tilt camera designed specifically to work with the Alarm.com hosted video service, which provides a professional surveillance solution without the complexity of traditional CCTV systems. High-quality Live and Recorded video are available to customers through web-enabled computers, cell phone web browsers or via free downloadable apps for iPhone, Blackberry and Android devices. Users can set and recall "preset" views or manually pan and tilt the camera through their web browser.



Features

Live resolution options	640x480, 320x240, 176x144
Recording resolution options	640x480, 320x240
Live quality	High, medium and low compression options
Recording quality	High and medium compression options
Recording compression	MPEG-4
Image sensor	1/4" CMOS, progressive scan
Iris	Fixed, f=4.5mm, F2.8
Field of view	43.6 (H) x 33.4 (V) degrees
Low-light sensitivity	1.0 lux @ F2.0
Image adjustments	Brightness, Contrast, Saturation, Sharpness, Exposure
Pan/Tilt range	+45 to -45 Pan, +22 to -35 Tilt
Video motion detection	3 windows, adjustable sensitivity and threshold
Digital input trigger	Yes
Ethernet connection	10/100 Mbps RJ-45
Wireless encryption	WEP, WPA or WPA2
Password authentication	"Digest" authentication
Simultaneous viewers	5
Private Button	Yes
Operation temperature	32° ~ 104° F (0° ~ 40° C)
Operating humidity	20% ~80% RH
Max power consumption	12V DC @ 1.1 amps
Dimensions (DxWxH)	3.2" x 3.3" x 3.9"
Weight	10.0 oz.

Included Accessories

- Quick install guide
- Power adapter
- Back cover
- Mounting stand and screws

Optional Extra Accessories

- ADC-VPE (9' DC power extension cable)