

# 5800WAVE

## WIRELESS SIREN



Honeywell's 5800WAVE is a fully wireless siren that provides periodic status information and battery back up for an added level of performance and protection. The flexible design simplifies installation, saves time and installs in seconds at any location without the need to run wires. System status is shown on the 5800WAVE with three LED's directly on the front of the unit.

## FEATURES

- Siren output level is 95 dB at three feet
- Transmits module status, including mounting tamper, low battery and AC loss to the control panel
- LED; show system status of the device
- AC powered with a rechargeable 12 hour battery backup
- Plugs in to any standard duplex receptacle and installs in seconds
- Provides temporal pulse sounding for fire alarms
- Lowers labor costs and saves time
- Simplifies installation
- Compatible with LYNXR (Rev 10 or higher) and VISTA controls that support the 5883 transceiver

## SPECIFICATIONS

- Dimensions: 4.5" W x 7.5" H x 2.25" D (114mm x 191mm x 57mm)
- Output Level: 95 dB at three feet
- Frequency of Operation: 345 MHz
- Input Voltage: 120VAC
- Current: 202mA Typical
- Operational Temperature 32° F to 122° F (0° to 50°C)

## ORDERING

5800WAVE Wireless Siren

### Honeywell Security & Communications

Honeywell  
2 Corporate Center Dr. Suite 100  
P.O. Box 9040  
Melville, NY 11747  
www.honeywell.com

# Honeywell

L/5800WAVE/D  
March 2008  
© 2008 Honeywell International Inc.